UAVSale

Aisheng ASN-216（LG-216A）Vertical Take-off and Landing UAV

MD-P00176 · md-aisheng-asn-216-lg-216a-vertical-take-off-and-landing-uav

ANS-216（LG-216A）Vertical Take-off and Landing UAV is a kind of system mainly used for environment monitoring, electricity power/oil pipeline patrol, railway patrol, surveying and mapping, border patrol etc. The UAV has feature of long endurance，high reliability, independent vertical take-off & landi

TECHNICAL SPECIFICATIONS

Long-distance transmission of HDI	50km control radius, 1080p high definition image transmission.
Max.Take-off Weight	30kg
Cruising Speed	80-100km/h
Max.Speed	120km/h
Service Ceiling	5000m
Endurance	＞4h
Payload	4kg
Control Radius	50km
Take-off and Landing Modes	Independent Vertical Take-off & Landing
Length	2220mm
Wing Span	3200mm

CERTIFICATION

Certification status is confirmed per order and is not published in the catalogue listing. Request the current declaration, test reports or conformity certificates from our sourcing team.

ORDERING INFORMATION

Model	Aisheng ASN-216（LG-216A）Vertical Take-off and Landing UAV
Part number	MD-P00176
Lead time	30 days
Minimum order	1 unit
Supply	made_to_order

Generated from the UAVSale product catalogue. Figures are manufacturer-supplied and subject to configuration. For the current revision and full documentation set, contact our sourcing team.