UAVSale

Flight Control for Target Drones (≤280m/s)

MD-P00252 · md-flight-control-for-target-drones-280m-s

Flight Control for Target Drones

TECHNICAL SPECIFICATIONS

Flight speed	80m/s / 180 m/s / 280 m/s / 80 m/s / 180 m/s / 280 m/s
Flight aultitude	10000m
Accuracy of flight position	2m
Flight elevation accuracy	5m
Flight altitude accurancy	1.5
Flying ship directional accuracy	土 2.5
analog input	3
Digital input	2 / 4
Digital output	6 / 6
PWM outoput	14
SBUS input and output	Support
RS232 Serial Interface	4 / 6
Other communication	Expandable 1way CAN
Number of destinations	1024 (Expandable)
POSdata storage	8192 (Expandable〉
control mode	Telecontrol mode、Stabilization mode、autonomous mode
reliability standard	6JB1S0A, GJB151B
Digital link distance	60km
weight	190g / i6〇 g
voltage	8-30V / 8-48V
Power cosumption	3W / 3W
operating temperature	-40 〜+70°C
storage temperature	.-55 〜+85* C

CERTIFICATION

Certification status is confirmed per order and is not published in the catalogue listing. Request the current declaration, test reports or conformity certificates from our sourcing team.

ORDERING INFORMATION

Model	Flight Control for Target Drones (≤280m/s)
Part number	MD-P00252
Lead time	30 days
Minimum order	1 unit
Supply	made_to_order

Generated from the UAVSale product catalogue. Figures are manufacturer-supplied and subject to configuration. For the current revision and full documentation set, contact our sourcing team.