UAVSale

High Speed Target Drone WF-B3A

MD-P00233 · md-high-speed-target-drone-wf-b3a

High Speed Target Drone WF-B3A

TECHNICAL SPECIFICATIONS

Length	4.05m
Wingspan	2.2m
Max Speed	900km/h (5,000 m MSL)
Altitude	50 m AGL to 12,000 m MSL
Sea-skimming Altitude	2.5 m AGL(Special altimeter is required)
Maneuverability	8g (5,000 m MSL)
Endurance	Up to 60 minutes
Operating Radius	Up to 300 km(intervisibility)
Control Mode	Autonomous and Remote control
Launch Method	Rocket-assisted
Recovery Method	Parachute
Payload Capacity	Over 30 kg
Fuel	RP-3
Service life	10 sorties
Payloads	Jammer, Seeker Simulator, Infrared or Chaff Jamming Bombs, Active or Passive Radar Augmentation, Miss-Distance Indicator, etc.
Typical tactical maneuvers	Lateral Maneuver, S Maneuver, Half Roll, Barrel Roll , Multi aircrafts coordination fleet, etc.

CERTIFICATION

Certification status is confirmed per order and is not published in the catalogue listing. Request the current declaration, test reports or conformity certificates from our sourcing team.

ORDERING INFORMATION

Model	High Speed Target Drone WF-B3A
Part number	MD-P00233

Lead time	30 days
Minimum order	1 unit
Supply	made_to_order

Generated from the UAVSale product catalogue. Figures are manufacturer-supplied and subject to configuration. For the current revision and full documentation set, contact our sourcing team.