UAVSale

HKP-260 UAV Photoelectric Turret

MD-P00439 · md-hkp-260-uav-photoelectric-turret

The HKP-260 photoelectric turret can be installed on medium-sized UAVs to perform search, reconnaissance, surveillance and guidance tasks.

TECHNICAL SPECIFICATIONS

EOT-220A photoelectric turret	1 unit;
220 HD tracking box	1;
Test cable	1 set;
Place tooling	1 set;
Photoelectric turret	7.5kg;
Direction	360 n ;
Pitch	-120 ～+90 ;
Azimuth	90 /s;
DC	+24V (20V～25.2V); ripple: 100mV.
Constant value	30W, peak value: 100W.
Working temperature	-40°C～+60°C;
Storage temperature	-55°C～+70°C.

CERTIFICATION

Certification status is confirmed per order and is not published in the catalogue listing. Request the current declaration, test reports or conformity certificates from our sourcing team.

ORDERING INFORMATION

Model	HKP-260 UAV Photoelectric Turret
Part number	MD-P00439
Lead time	30 days
Minimum order	1 unit
Supply	made_to_order

Generated from the UAVSale product catalogue. Figures are manufacturer-supplied and subject to configuration. For the current revision and full documentation set, contact our sourcing team.