UAVSale

HKP-350 UAV Electro-Optical/Infrared Turret

MD-P00438 · md-hkp-350-uav-electro-optical-infrared-turret

HKP-350 UAV Electro-Optical/Infrared Turret is equipped with a variety of optical sensors such as infrared cameras, visible light cameras and laser irradiators, and has the function of isolating the movement of the carrier to keep the line of sight stable in the inertial space; it can be mounted on

TECHNICAL SPECIFICATIONS

Number of CCD pixels	2.38 million;
Number of pixels	1920 1080;
Pixel size	3.75um 3.75um
Detector size	1/1.9 inch
Optical focal length	800mm fixed focus;
Horizontal angle of view	0.47 ;
Detection distance	ambient temperature 25°C, relative humidity 80%, visibility greater than 20Km
Azimuth	n 360 ;
Pitch	-150 ～+90 . (+90 for favorites)
Photoelectric turret	60Kg;
Power consumption	constant value 150W, peak value 800W.
Working temperature	-40℃~+60℃;
Storage temperature	-55℃~+70℃.

CERTIFICATION

Certification status is confirmed per order and is not published in the catalogue listing. Request the current declaration, test reports or conformity certificates from our sourcing team.

ORDERING INFORMATION

Model	HKP-350 UAV Electro-Optical/Infrared Turret
Part number	MD-P00438
Lead time	30 days
Minimum order	1 unit
Supply	made_to_order

Generated from the UAVSale product catalogue. Figures are manufacturer-supplied and subject to configuration. For the current revision and full documentation set, contact our sourcing team.