UAVSale

RZ-60 Gps Deceptive Jammer

MD-P00361 · md-rz-60-gps-deceptive-jammer

RZ-60 GPS deception jammer can generate different types of interference waveforms to suppress, forward deception and combined interference to GPS receiver; For different civil GPS receivers, military GPS receivers, GPS military code direct acquisition receivers and GPS receivers equipped with adapti

TECHNICAL SPECIFICATIONS

Interference power	not less than 40W (adjustable)
Interference frequency points	L1 / L2 / L5 / B1 / B2 / B3, etc. (interference frequency points can be expanded)
Interference waveform	point frequency interference, broadband noise interference, pulse interference
Jamming strategy	single point jamming or multi-point jamming
Jamming mode	suppression jamming, forwarding deceptive jamming and combined jamming
Receiving antenna	GPS dual band antenna
Transmitting antenna	Standard horn antenna
Volume of receiver equipment	length / width / height 270mmx200mmx50mm
Weight of receiver equipment	2kg
Volume of jammer equipment	length / width / height 350mm x 230mm x 170mm
Jammer equipment weight	14kg
Operating temperature	- 40-55 °C
Storage temperature	- 55-75 °C

CERTIFICATION

Certification status is confirmed per order and is not published in the catalogue listing. Request the current declaration, test reports or conformity certificates from our sourcing team.

ORDERING INFORMATION

Model	RZ-60 Gps Deceptive Jammer
Part number	MD-P00361
Lead time	30 days
Minimum order	1 unit
Supply	made_to_order

Generated from the UAVSale product catalogue. Figures are manufacturer-supplied and subject to configuration. For the current revision and full documentation set, contact our sourcing team.