UAVSale

S-25 Rocket

MD-P00750 · md-s-25-rocket

The S-25 rocket (Russian: С-25) is a series of aerial rocket systems developed by the Soviet Air Force and used by military aircraft against semi-hard and hard ground targets. It still serves in the Russian Air Force and various export customers.

TECHNICAL SPECIFICATIONS

Date of development	Mid-1960s - 1975
Date of production	1975 - present
Weight	480 kg (1,058.22 lb)
Length	3,310-3,800 mm (130.31-149.61 in)
Body	250 mm (9.84 in)
Warhead	300-420 mm (11.81-16.54 in)
Effective range	3,000-11,000 m (3,280.84-12,029.75 yd, 9,842.52-36,089.24 ft, 1.86-6.84 mi)
Detonation mechanism	trigger fuse or proximity fuse
Engine	Rocket engine
Wingspan	600 mm (23.62 in)
Speed	511-700 m/s, about 1.5-2.06 Mach
Guidance system	unguided/laser guidance system
S-25F	Models equipped with high explosive warheads, range 2,000-3,000 m.
S-25O	Model equipped with fragmentation warhead and radio proximity fuze.
S-25O-PU	Model equipped with a cone charge warhead.
S-25OF	Model with high blaster warheads. (Russian: Осколочно-фугасный снаряд).
S-25OFM	Model for enhanced targets.
S-25M	A modernized version of the S-25OF.
S-25MD	Modernized version with extended range of 4,000-5,000 m.
S-25L	laser-guided version, Bunker buster, ground-penetrating warhead version with a range of 7,000 m.
S-25LD	laser-guided and extended range version with a range of 11,000 m.
S-25TV	Model with Television guidance head, mainly for export.
S-25IRS	Model with infrared guidance head.

S-25A	The model of active radar guidance head with Ku-band (18-40 GHZ) active radar guidance.
S-25SE	Equipped with the Glonass system

CERTIFICATION

Certification status is confirmed per order and is not published in the catalogue listing. Request the current declaration, test reports or conformity certificates from our sourcing team.

ORDERING INFORMATION

Model	S-25 Rocket
Part number	MD-P00750
Lead time	30 days
Minimum order	1 unit
Supply	made_to_order

Generated from the UAVSale product catalogue. Figures are manufacturer-supplied and subject to configuration. For the current revision and full documentation set, contact our sourcing team.