UAVSale

TeleD30 UAV Data Link

MD-P00373 · md-teled30-uav-data-link

The teleD30 data link can be used as the data transmission channel for UAV remote control and telemetry. It can realize the functions of self frequency hopping, configurable transmission rate, pairing, encryption and so on. It has the characteristics of strong anti-interference, long transmission di

TECHNICAL SPECIFICATIONS

Maximum operating distance	30km
Operating frequency	841mhz ~ 845mhz
User data rate	153.6kbps (remote control and telemetry data)
Airborne data interface	RS-232 2，RS-422 one
Ground data interface	RS-422 1. Ethernet one
Antenna form	ground omnidirectional, airborne omnidirectional
Operating temperature	- 20 ℃ ~ + 55 ℃
Power supply for airborne equipment	dc9 ~ 36V, 6W
Weight of airborne equipment	data terminal 200g
Size of airborne equipment	107mm 103mm 21mm

CERTIFICATION

Certification status is confirmed per order and is not published in the catalogue listing. Request the current declaration, test reports or conformity certificates from our sourcing team.

ORDERING INFORMATION

Model	TeleD30 UAV Data Link
Part number	MD-P00373
Lead time	30 days
Minimum order	1 unit
Supply	made_to_order

Generated from the UAVSale product catalogue. Figures are manufacturer-supplied and subject to configuration. For the current revision and full documentation set, contact our sourcing team.