UAVSale

TeleV15 UAV Wireless Data Transmission and Image Transmission Integrated Data Link (with Networking Function)

MD-P00374 · md-telev15-uav-wireless-data-transmission-and-image-transmission-integrated-data-li

The tele V15 data link is a data transmission and picture transmission integrated mode, which can realize the functions of frequency hopping, diversity reception, configurable transmission rate, pairing and encryption. It has the characteristics of strong anti multipath ability, light weight, low po

TECHNICAL SPECIFICATIONS

Maximum operating distance	15km
Operating frequency	806MHz ~ 825mhz; 1.4GHz，2.4GHz
User data rate	5mbps (remote control + telemetry + image transmission)
Airborne data interface	RS-232 1，RS-422 1. Ethernet one
Ground data interface	RS-422 1. Ethernet one
Antenna form	ground omnidirectional 2. Airborne omnidirectional 2 (or 1)
Operating temperature	- 20 ℃ ~ + 55 ℃
Power supply for airborne equipment	dc5 ~ 15V, s5w
Weight of airborne equipment	data terminal 350g
Size of airborne equipment	< 124mmx120mm 15mm

CERTIFICATION

Certification status is confirmed per order and is not published in the catalogue listing. Request the current declaration, test reports or conformity certificates from our sourcing team.

ORDERING INFORMATION

Model	TeleV15 UAV Wireless Data Transmission and Image Transmission Integrated Data Link (with Networking Function)
Part number	MD-P00374
Lead time	30 days
Minimum order	1 unit
Supply	made_to_order

Generated from the UAVSale product catalogue. Figures are manufacturer-supplied and subject to configuration. For the current revision and full documentation set, contact our sourcing team.