UAVSale

# TeleV200 UAV Data Transmission and Image Transmission Integrated Data Link

MD-P00379 · md-telev200-uav-data-transmission-and-image-transmission-integrated-data-link

The data link of telev200 UAV is an integrated mode of data transmission and image transmission, which can realize ground directional antenna tracking, radio positioning, radio ranging, azimuth measurement and MIMO 2 2. The transmission rate can be configured, paired, encrypted and other functions.

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Maximum operating distance** | 200km |
| **Operating frequency** | 1430-1444mhzmhz |
| **User data rate** | 5mbps (remote control + telemetry + image transmission) |
| **Airborne data interface** | RS-232 2，RS-422 1. Ethernet one |
| **Ground data interface** | Ethernet one |
| **Antenna form** | ground oriented, airborne omnidirectional 2 (or 1) |
| **Operating temperature** | - 40 ℃ ~ + 55 ℃ |
| **Power supply for airborne equipment** | dc9 ~ 36V, s80w |
| **Weight of airborne equipment** | data terminal |

## CERTIFICATION

*Certification status is confirmed per order and is not published in the catalogue listing. Request the current declaration, test reports or conformity certificates from our sourcing team.*

## ORDERING INFORMATION

| | |
|---|---|
| **Model** | TeleV200 UAV Data Transmission and Image Transmission Integrated Data Link |
| **Part number** | MD-P00379 |
| **Lead time** | 30 days |
| **Minimum order** | 1 unit |
| **Supply** | made_to_order |

Generated from the UAVSale product catalogue. Figures are manufacturer-supplied and subject to configuration. For the current revision and full documentation set, contact our sourcing team.