UAVSale

TeleV50 UAV Data Link

MD-P00375 · md-telev50-uav-data-link

Teled50 UAV data link is usually used as the data transmission channel of UAV remote control and telemetry. It can realize the functions of self frequency hopping, configurable transmission rate, pairing, encryption and so on. It has the characteristics of strong anti-interference, long transmission

TECHNICAL SPECIFICATIONS

Maximum operating distance	50km
Operating frequency	840.5mhz ~ 845mhz
User data rate	115.2kbps (remote control and telemetry data)
Airborne data interface	RS-232 2，RS-422 one
Ground data interface	RS-422 1. Ethernet one
Antenna form	ground omnidirectional, airborne omnidirectional
Operating temperature	- 40 ℃ ~ + 55 ℃
Power supply for airborne equipment	dc9 ~ 36V, s6w
Weight of airborne equipment	data terminal 200g
Size of airborne equipment	107mm 103mm 21mm

CERTIFICATION

Certification status is confirmed per order and is not published in the catalogue listing. Request the current declaration, test reports or conformity certificates from our sourcing team.

ORDERING INFORMATION

Model	TeleV50 UAV Data Link
Part number	MD-P00375
Lead time	30 days
Minimum order	1 unit
Supply	made_to_order

Generated from the UAVSale product catalogue. Figures are manufacturer-supplied and subject to configuration. For the current revision and full documentation set, contact our sourcing team.