UAVSale

# Tracked Unmanned Ground Vehicle Chassis KKF60

MD-P00310 · md-tracked-unmanned-ground-vehicle-chassis-kkf60

KT60 tracked unmanned ground vehicle chassis is a has a good stability and cross-country ability of medium-sized pedrail robot chassis, represent a stability, it can realize spin around, the vehicle use classic Christian type independent suspension design, unilateral 4 groups of suspension arm + sin

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Overall dimensions** | 756*675*309mm |
| **Track width** | 80mm |
| **Grounding length** | 360+10mm |
| **Chassis weight** | 5okg |
| **Rated load** | 60kg |
| **Main body material** | Alloy steel plate/stainless steel plate/aluminum plate |
| **Caterpillar material** | Premium rubber inserts kevlar |
| **Wheels** | Aluminum alloy |
| **Surface treatment** | Spray plastic/paint |
| **Motor power** | 200w * 2 |
| **Working temperature** | - 20 ℃ ~ 60 ℃ |
| **speed** | 0~1m/s |
| **Biggest obstacle** | 60mm |
| **Biggest climbing** | 30 (light) |
| **Control distance** | 300 m() |
| **Endurance** | 100 min (light) |
| **Battery** | Lithium battery 48V, 40AH |
| **Charging time** | 2 to 3 hours |

## CERTIFICATION

*Certification status is confirmed per order and is not published in the catalogue listing. Request the current declaration, test reports or conformity certificates from our sourcing team.*

## ORDERING INFORMATION

| | |
|---|---|
| **Model** | Tracked Unmanned Ground Vehicle Chassis KKF60 |
| **Part number** | MD-P00310 |
| **Lead time** | 30 days |
| **Minimum order** | 1 unit |
| **Supply** | made_to_order |

Generated from the UAVSale product catalogue. Figures are manufacturer-supplied and subject to configuration. For the current revision and full documentation set, contact our sourcing team.